

INDUSTRIAL COMPONENT DATA

IAK 16 2715982 PHOENIX CONTACT Branch terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IAK 16



Manufacturer	PHOENIX CONTACT
MPN / Reference	IAK 16
Catalog number	2715982
Category	Busbar terminal
Minimum order	50 Pcs
Document ID	EO-4D3D3F36C8
Generated	2026-08-04

Product Overview

Branch terminal

Branch module, rated current: 57 A, connection type: Screw connection, cross-section: 0.5 mm² - 16 mm², colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 2715982

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 254 (CL-2005)

GTIN 4017918061739

Weight per Piece (excluding packing) 13.130 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Color gray

Maximum load current 76 A

Nominal current IN 57 A

Maximum load current 76 A (with 16 mm² conductor cross section)

Dimensions

Length 22.9 mm

Width 7.7 mm

Connection data

Conductor cross section solid min. 0.5 mm²

Conductor cross section solid max. 16 mm²

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 10 mm²

Conductor cross section AWG min. 20

Conductor cross section AWG max. 6

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm²

2 conductors with same cross section, solid min. 0.5 mm²

2 conductors with same cross section, solid max. 10 mm²

2 conductors with same cross section, stranded min. 0.5 mm²

2 conductors with same cross section, stranded max. 10 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. 10 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IAK 16 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.