

INDUSTRIAL COMPONENT DATA

IB IL 24 DO 4/EF-ECO 2702825 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL 24 DO 4/EF-ECO



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL 24 DO 4/EF-ECO
Catalog number	2702825
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-27935A6EAD
Generated	2026-08-04

Product Overview

Inline terminal

Inline, Digital output module, Digital outputs:4, 24 VDC, connection technology:3 conductors, transmission speed on the local bus:500 kBit/s, protection index: IP20, Inline connector included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2702825

Packing unit 1 pc

Catalog page Page 141 (C-6-2017)

GTIN 4055626381473

Weight per Piece (excluding packing) 83.850 g

Custom tariff number 85389099

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Dimensional drawing

Width 12.2 mm

Height 119.8 mm

Depth 71.5 mm

Ambient conditions

Ambient temperature (operation) 0 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (according to DIN EN 61131-2)

Permissible humidity (storage/transport) 10 % ... 95 % (according to DIN EN 61131-2)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

Connection data

Designation Inline connector

Connection method Spring-cage connection

Conductor cross section solid min. 0.08 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.08 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section AWG min. 28

Conductor cross section AWG max. 16

Stripping length 8 mm

General

Mounting type DIN rail

Net weight 83.85 g

Note on weight specifications with connector

Diagnostics messages Short-circuit / overload of the digital outputs Error message in the diagnostic code (bus) and display (2 Hz) via the LED (D) on the module

Interfaces

Designation Inline local bus

No. of channels 2

Connection method Inline data jumper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL 24 DO 4/EF-ECO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.