

INDUSTRIAL COMPONENT DATA

IC 2,5/12-GF-5,08 AU 1026758 PHOENIX CONTACT

Printed-circuit board connector IC 2,5/12-GF-5,08 AU 1026758

Brand: PHOENIX CONTACT | Manufacturer Part Number: IC 2,5/12-GF-5,08 AU

LAPP KABEL STUFGART. ÖLFLEX® CHAIN 805 CY (1

Manufacturer	PHOENIX CONTACT
MPN / Reference	IC 2,5/12-GF-5,08 AU
Catalog number	1026758
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-73EEC9E662
Generated	2026-08-06

Product Overview

Printed-circuit board connector - IC 2,5/12-GF-5,08 AU - 1026758

Printed circuit board base housing, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Gold, contact type: Female, number of potentials: 12, number of rows: 1, number of poles: 12, number of connections: 12, family of articles: IC 2.5/.. -GF, pitch: 5.08 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of solder pins per potential: 2, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: Screw lock, fixing type: Air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 12, pitch: 5.08 mm, color: green, contact surface: Gold, mounting: Wave soldering

Key Commercial Data

Orderkey 1026758

Packing unit 1

GTIN 4055626518992

Custom tariff number 85366930

Dimensions

Length [L] 18.9 mm

Width 71.08 mm

Pitch 5.08 mm

Dimension a 55.88 mm

Width [w] 71.08 mm

Height [h] 13.7 mm

Height 10.2 mm

Length of the solder pin 3.5 mm

Pin dimensions 1.2 x 0.5 mm

Pin spacing 5.04 mm

Length 18.9 mm

General

Range of articles IC 2,5/...-STF

Color green

Number of positions 12

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss

eCl@ss 5.1 27260700

eCl@ss 6.0 27260700

eCl@ss 7.0 27440402

eCl@ss 8.0 27440402

eCl@ss 9.0 27440402

ETIM

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IC 2,5/12-GF-5,08 AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.