


INDUSTRIAL COMPONENT DATA

MVSTBR 2,5/ 4-ST-5,08 AU BD:X3 1712399 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MVSTBR 2,5/ 4-ST-5,08 AU BD:X3



Manufacturer	PHOENIX CONTACT
MPN / Reference	MVSTBR 2,5/ 4-ST-5,08 AU BD:X3
Catalog number	1712399
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-6A04FDCD22
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Gold, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MVSTBR 2.5/.. -ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, connection direction conductor/printed circuit board: 90 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1712399

Packing unit 1

GTIN 4055626287492

Custom tariff number 85366990

Dimensions

Pitch 5.08 mm

Dimension a 15.24 mm

General

Range of articles MVSTBR 2,5/..-ST

Number of positions 4
Connection method Screw connection with tension sleeve
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/2) 320 V
Rated voltage (II/2) 630 V
Nominal current I_N 12 A
Nominal cross section 2.5 mm²
Internal cylindrical gage A3
Stripping length 7 mm
Screw thread M3
Tightening torque, min 0.5 Nm
Tightening torque max 0.6 Nm
Environmental Product Compliance
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
Classifications
eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440309eCl@ss 8.027440309eCl@ss 9.027440309
ETIM 5.0EC002638ETIM 6.0EC002638
ETIM for 1712399 Connectors (EC002638)
Feature Name
Feature Value
Type of connection (EF000064)
Other
Contact type (EF001587)
Bus
Number of poles (EF001391)
4
Number of plug-in contact rows (EF006935)
1
Modular spacing contacts (EF007326)
5.08 mm
Modular spacing connections (EF006827)
5.08 mm
Angle contact/conductor connection (EF007546)
Other
Rated current I_n (EF008250)
12 A
Rated voltage (EF000228)
320 V
Rated surge voltage (EF002993)
4 kV
Over voltage category (EF006785)
III
Pollution degree (EF006786)
2

Connectable conductor cross section fine-strand without cable...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MVSTBR 2,5/ 4-ST-5,08 AU BD:X3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.