

INDUSTRIAL COMPONENT DATA

ICC25-H/4L5,0-7035 2203902 PHOENIX CONTACT

Feed-through header

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICC25-H/4L5,0-7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICC25-H/4L5,0-7035
Catalog number	2203902
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-035FD115E7
Generated	2026-08-03

Product Overview

Feed-through header

Printed circuit board base housing, nominal section: 2.5 mm², color: bright gray, nominal current: 16 A, nominal voltage (III/2): 320 V, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: ICC..-H/..L5,0, pitch: 5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of welding pins per potential: 1, Plug-in face orientation: Standard, locking: Snap lock, fixing type: without, packaging type: Carton packing, Item with left side pin output

PCB headers, nominal cross section: 2.5 mm², color: light gray, nominal current: 16 A, rated voltage (III/2): 320 V, contact surface: Sn, contact connection type: Pin, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: ICC..-H/..L5,0, pitch: 5 mm, mounting: Wave soldering, pin layout: Linear pinning, solder pin [P]: 3.5 mm, number of solder pins per potential: 1, plug-in system: ICC 2,5, Pin connector pattern alignment: Standard, locking: Snap-in locking, mounting: without, type of packaging: Box packaging, Product with pin output on left side

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type PCB headers

Product family ICC..-H/..L5,0

Type Header perpendicular to the PCB

Number of positions 4

Pitch 5 mm

Number of connections 4
Number of rows 1
Number of potentials 4
Mounting flange without
Pin layout Linear pinning
Solder pins per potential 1
Data management status
Article revision 02
Electrical propertiesNominal current I_N 16 A
Nominal voltage U_N 320 V
Contact resistance 1.5 m Ω
Rated voltage (III/3) 250 V
Rated surge voltage (III/3) 4 kV
Rated voltage (III/2) 320 V
Rated surge voltage (III/2) 4 kV
Rated voltage (II/2) 630 V
Rated surge voltage (II/2) 4 kV
MountingMounting type Wave soldering
Pin layout Linear pinning
Material specificationsMaterial data - contact
Note WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201
Contact material Cu alloy
Surface characteristics Tin-plated
Metal surface terminal point (top layer) Tin (2 - 4 μm Sn)
Metal surface terminal point (middle layer) Nickel (1.3 - 3 μm Ni)
Metal surface contact area (top layer) Tin (2 - 4 μm Sn)
Metal surface contact area (middle layer) Nickel (1.3 - 3 μm Ni)
Metal surface soldering area (top layer) Tin (2 - 4 μm Sn)
Metal surface soldering area (middle layer) Nickel (1.3 - 3 μm Ni)
Material data - housing
Color (Housing) light gray (7035)
Insulating material PA
Insulating material group I
CTI according to IEC 60112 600
Flammability rating according to UL 94 V0
Glow wire flammability index GWFI according to EN 60695-2-12 850
Gl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICC25-H/4L5,0-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.