


INDUSTRIAL COMPONENT DATA

ICC25-H/4R5,0-5015 1071449 PHOENIX CONTACT PCB headers, number of positions: 4, pitch: 5 mm, color: sky blue..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICC25-H/4R5,0-5015



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICC25-H/4R5,0-5015
Catalog number	1071449
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-A8D3257C82
Generated	2026-08-05

Product Overview

PCB headers, number of positions: 4, pitch: 5 mm, color: sky blue, solder pin [P]: 3.5 mm, Article with lateral pin exit
Printed circuit board base housing, nominal section: 2.5 mm², color: blue, nominal current: 16 A, nominal voltage (III/2): 320 V, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, article family: ICC.. -H/.. R5.0, pitch: 5 mm, mounting: Wave welding, pin arrangement: Linear pin arrangement, pin length [P]: 3.5 mm, number of welding pins per potential: 1, Plug-in face orientation: Standard, locking: Snap lock, fixing type: without, packaging type: Carton packing, Item with right side pin output

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1071449

Packing unit 1 pc

Minimum order quantity 50 pc

GTIN 4055626751788

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85366930

Country of origin PL (Poland)

Drawings

General

[Classifications](#)

[Dimensions](#)

[Standards and Regulations](#)

[Drawings](#)

[Diagram](#)

Type: PSPT 2,5/...-ST ... with ICC20(25)-H/...L(R)5,0-...

[Diagram](#)

Type: MSTBT 2,5 HC/...-STF with ICC20(25)-H/...L(R)5,0-...

[Back to top](#)[Dimensions](#)

Length [l] 20.35 mm

Width 25 mm

Pitch 5 mm

Width [w] 25 mm

Height [h] 22.4 mm

Length of the solder pin 3.5 mm

Length 20.35 mm

[Back to top](#)[General](#)

Range of articles ICC25-H/..R

Insulating material group I

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Insulating material PA

Flammability rating according to UL 94 V0

Color sky blue

Number of positions 4

[Back to top](#)[Standards and Regulations](#)

Flammability rating according to UL 94 V0

[Back to top](#)[Classifications](#)

eCI@ss

eCI@ss 5.1 27260700

eCI@ss 6.0 27260700

eCI@ss 7.0 27440402

eCI@ss 8.0 27440402

eCI@ss 9.0 27440402

[Back to top](#)[ETIM](#)

ETIM 5.0 EC002637

ETIM 6.0 EC002637

ETIM 7.0 EC002637

[Back to top](#)

ETIM for 1071449 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Pin

Number of poles (EF001391)

4

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

5 mm

Modular spacing connections (EF006827)

5 mm

Rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICC25-H/4R5,0-5015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.