

**INDUSTRIAL COMPONENT DATA**

# ICC25-TP2,5/4L5,0-5015 1477322 PHOENIX CONTACT Printed circuit board terminal, nominal current: 18 A, nomina..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICC25-TP2,5/4L5,0-5015

|                                                                                   |                 |                                |
|-----------------------------------------------------------------------------------|-----------------|--------------------------------|
|  | Manufacturer    | PHOENIX CONTACT                |
|                                                                                   | MPN / Reference | ICC25-TP2,5/4L5,0-5015         |
|                                                                                   | Catalog number  | 1477322                        |
|                                                                                   | Category        | Printed circuit board terminal |
|                                                                                   | Minimum order   | 50 Pcs                         |
|                                                                                   | Document ID     | EO-16A64BEF93                  |
|                                                                                   | Generated       | 2026-08-06                     |

## Product Overview

Printed circuit board terminal, nominal current: 18 A, nominal voltage (III/2): 300 V, nominal section: 2.5 mm<sup>2</sup>, number of potentials: 4, number of rows: 1, number of poles per row: 4, article family: ICC.. -TP2.5/.. L5.0, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: blue, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.15 mm, number of solder pins per potential: 1, packaging type: boxed. Item with side pin output on the left

Printed circuit board terminal, rated current: 18 A, rated voltage (III/2): 300 V, rated cross-section: 2.5 mm<sup>2</sup>, number of potentials: 4, number of rows: 1, number of poles per row: 4, article family: ICC.. -TP2.5/.. L5.0, pitch: 5 mm, connection type: Push-in spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 0 °, color: blue, Pin arrangement: Linear pin arrangement, number of solder pins per potential: 1, packaging type: boxed packaging. Item with side pin output on the left

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

ETIM for 1477322 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

22.4 mm

Number of electrical connections (EF008252)

4

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5 mm

Rated current  $I_n$  (EF008250)

18 A

Rated voltage (EF000228)

300 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Spring clamp connection

Connectable conductor cross section solid-core (EF007337)

0.2 mm<sup>2</sup>

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm<sup>2</sup>

Connectable conductor cross section fine-strand without cable end sleeve (EF007341)

0.2 mm<sup>2</sup>

Connectable conductor cross section multi-wired (EF007343)

2.5 mm<sup>2</sup>

Connection type PCB (EF006822)

Soldering connection

Material connection surface (EF006826)

Tin

Diameter connection pin (EF006823)

1.4 mm

Material insulation body (EF007543)

Other

Housing colour (EF000136)

Blue

Inflammability class of insulation material according to UL94 (EF002521)

V0

Operating temperature (EF002393)

-40 °C

Type of PCB fastening (EF008226)

Connecting contact

Type of fastening (EF002442)

Solder

Type of banding (EF007011)

Carton (for SMD)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICC25-TP2,5/4L5,0-5015 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.