

INDUSTRIAL COMPONENT DATA

ICS20-B100X98-O-9005 1355950 PHOENIX CONTACT Rail housing, Lower part of the housing with metal pin, width: ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS20-B100X98-O-9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS20-B100X98-O-9005
Catalog number	1355950
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-5010C192DB
Generated	2026-08-06

Product Overview

Rail housing, Lower part of the housing with metal pin, width: 20 mm, height: 100 mm, depth: 108.35 mm, color: black (Similar RAL 9005), cross bridge: Bus connector for rail (optional), number of poles cross connector: 8

DIN rail housing, Lower housing part with metal foot catch, width: 20 mm, height: 100 mm, depth: 108.35 mm, color: black (9005), cross connection: DIN rail connector (optional), number of positions cross connector: 8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesGeneral Refer to the data sheet for the range in the download area.

General Material of contact pads for bus connector, galvanic gold (hard gold)

Product propertiesProduct type Enclosure bottom part

Product family ICS20-...100X..

Max. number of positions 24 (pitch: 5 mm)

32 (pitch: 3.5 mm)

Number of rows 4

Type Lower housing part with metal foot catch

Housing type DIN rail housing

Ventilation openings present no

Housing series ICS

Connection dataCross section AWG (converted acc. to IEC)

Dimensions Dimensional drawing

Width 20 mm

Height 100 mm

Depth 108.35 mm

Depth from top edge of DIN rail to support point on upper part 98.15 mm

Dimensions 20 mm x 100 mm x 110 mm (Lower housing part from the top edge of the DIN rail with upper housing part)

20 mm x 100 mm x 116.7 mm (Lower housing part with upper housing part)

PCB design

PCB thickness 1.4 mm ... 1.8 mm

Material specifications Color black (9005)

Flammability rating according to UL 94 V0

CTI according to IEC 60112 600

Surface characteristics untreated

Housing material Polyamide

Environmental and real-life conditions Power dissipation single housing for 20 °C

Ambient temperature 20 °C

Reduction factor 1

Mounting position vertical

Power dissipation 16 W

Power dissipation single housing for 30 °C

Ambient temperature 30 °C

Reduction factor 0.84

Mounting position vertical

Power dissipation 13.5 W

Power dissipation single housing for 40 °C

Ambient temperature 40 °C

Reduction factor 0.69

Mounting position vertical

Powe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS20-B100X98-O-9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.