

INDUSTRIAL COMPONENT DATA

ICS20-F45V-7035 1079493 PHOENIX CONTACT DIN rail housing, ICS filler, with vents, width: 20 mm, height: 7 mm..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS20-F45V-7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS20-F45V-7035
Catalog number	1079493
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-9A3E0F216D
Generated	2026-08-06

Product Overview

DIN rail housing, ICS filler, with vents, width: 20 mm, height: 7 mm, depth: 45 mm, color: light gray (7035)
Rail box, ICS plug, with ventilation slits, width: 20 mm, height: 7.25 mm, depth: 44.9 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1079493
Packing unit 1
GTIN 4055626799926
Custom tariff number 85389099
Item properties
Material data
General information
Standards and regulations
Dimensions
Ambient conditions
Packaging information
Classifications
Item properties

Brief article description Connection plate

Type ICS20-F45V-7035

Order No. 1079493

Housing type DIN rail housing

Type ICS filler, with vents

Mounting type Slot

Ventilation openings present yes

Back to topDimensions

Width [w] 20 mm

Height [h] 7 mm

Depth [d] 45 mm

Back to topMaterial data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polyamide

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

Back to topGeneral information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

Back to topPackaging information

Pieces per package 10

Denomination packing units Pcs.

Outer packaging type Resealable bag

Back to topStandards and regulations

Flammability rating according to UL 94 V0

Back to topClassifications

eCl@ss

eCl@ss 5.1 27180506

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

Back to topETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

Back to top

ETIM for 1079493 Low-voltage industr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS20-F45V-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.