

INDUSTRIAL COMPONENT DATA

ICS20-F90S-1018 1287449 PHOENIX CONTACT DIN rail housing, ICS plug, closed, width: 20 mm, height: 7.25 mm, d..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS20-F90S-1018



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS20-F90S-1018
Catalog number	1287449
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-916B22900C
Generated	2026-08-03

Product Overview

DIN rail housing, ICS plug, closed, width: 20 mm, height: 7.25 mm, depth: 89.8 mm, colour: yellow (similar RAL 1018)

Rail box, ICS cap, closed, width: 20 mm, height: 7.25 mm, depth: 89.8 mm, colour: yellow (1018)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesGeneral Refer to the data sheet for the range in the download area.

Product propertiesProduct type Connection plate

Product family ICS20

Type ICS filler, closed

Housing type DIN rail housing

Ventilation openings present no

Housing series ICS

Connection dataCross section AWG (converted acc. to IEC)

DimensionsDimensional drawing

Width 20 mm

Height 7.25 mm

Depth 89.8 mm

PCB design

PCB thickness 1.4 mm ... 1.8 mm

Material specificationsColor yellow (1018)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Surface characteristics untreated
Housing material Polyamide
Environmental and real-life conditionsVibration test
Specification IEC 60068-2-6:2007-12
Frequency 10 - 150 - 10 Hz
Sweep speed 1 octave/min
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)
Acceleration 2g (58.1 Hz ... 150 Hz)
Test duration per axis 2.5 h
Test directions X-, Y- and Z-axis
Glow-wire test
Specification IEC 60695-2-11:2014-02
Temperature 850 °C
Time of exposure 30 s
Thermal stability / ball thrust test
Specification IEC 60695-10-2:2014-02
Temperature 125 °C
Test duration 1 h
Force 20 N
Mechanical strength / tumbling barrel
Specification IEC 60068-2-31:2008-05
Height of fall 50 cm
Frequency 50
Shocks
Specification IEC 60068-2-27:2008-02
Pulse shape Half-sine
Acceleration 15g
Shock duration 11 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Test for substances that would hinder coating with paint or varnish
Specification VDMA 24364:2018-05...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS20-F90S-1018 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.