

INDUSTRIAL COMPONENT DATA

ICS25-B100X120-O-7035 1355945 PHOENIX CONTACT Rail housing, Housing underside with metal pin, width: 25 mm, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-B100X120-O-7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-B100X120-O-7035
Catalog number	1355945
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-CFCC2C60DC
Generated	2026-08-06

Product Overview

Rail housing, Housing underside with metal pin, width: 25 mm, height: 100 mm, depth: 130.9 mm, colour: light grey (Similar RAL 7035), cross bridge: Rail bus connector (optional), number of cross connector poles: 8

Rail box, Bottom of housing with metal pin, width: 25 mm, height: 100 mm, depth: 130.9 mm, colour: light grey (7035), cross-bridge: Bus connector for rail (optional), number of poles cross connector: 8

DIN rail housing, Lower housing part with metal foot catch, width: 25 mm, height: 100 mm, depth: 130.9 mm, color: light grey (7035), cross connection: DIN rail connector (optional), number of positions cross connector: 8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesGeneral Refer to the data sheet for the range in the download area.

General Material of contact pads for bus connector, galvanic gold (hard gold)

Product propertiesProduct type Enclosure bottom part

Product family ICS25-..100X..

Max. number of positions 40 (pitch: 5 mm)

50 (pitch: 3.5 mm)

Number of rows 5

Type Lower housing part with metal foot catch

Housing type DIN rail housing

Ventilation openings present no

Housing series ICS

Connection data Cross section AWG (converted acc. to IEC)

Dimensions Dimensional drawing

Width 25 mm

Height 100 mm

Depth 130.9 mm

Depth from top edge of DIN rail to support point on upper part 120.7 mm

Dimensions 25 mm x 100 mm x 132.6 mm (Lower housing part from the top edge of the DIN rail with upper housing part)

25 mm x 100 mm x 139.2 mm (Lower housing part with upper housing part)

PCB design

PCB thickness 1.4 mm ... 1.8 mm

Material specifications Color light grey (7035)

Flammability rating according to UL 94 V0

CTI according to IEC 60112 600

Surface characteristics untreated

Housing material Polyamide

Environmental and real-life conditions Power dissipation single housing for 20 °C

Ambient temperature 20 °C

Reduction factor 1

Mounting position vertical

Power dissipation 17 W

Power dissipation single housing for 30 °C

Ambient temperature 30 °C

Reduction factor 0.81

Mounting position vertical

Power dissipation 13.5 W

Power dissipation single housing for 40 °C

Ambient temperature 40 °C

Reduction factor 0.67

Mounting position vertical...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-B100X120-O-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.