

INDUSTRIAL COMPONENT DATA

ICS25-C100X12-5015 1072378 PHOENIX CONTACT DIN rail housing, Upper part, closed, width: 25 mm, height: 100 m..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-C100X12-5015



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-C100X12-5015
Catalog number	1072378
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-2C55AF7F19
Generated	2026-08-04

Product Overview

DIN rail housing, Upper part, closed, width: 25 mm, height: 100 mm, depth: 12 mm, color: blue (5015)

Rail box, Top, closed, width: 25 mm, height: 100 mm, depth: 14.35 mm, colour: blue (5015)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1072378

Packing unit 1

GTIN 4055626764542

Custom tariff number 85389099

Item properties

Material data

Mechanical strength/tumbling barrel

Test for assessing the risk of fire (glow wire)

General information

Standards and regulations

Dimensions

Ambient conditions

Thermostability (Ball Thrust Test)

Test for substances that would hinder coating with paint or varnish

Packaging information

Classifications

Item properties

Brief article description Upper part of housing

Type ICS25-C100X12-5015

Order No. 1072378

Housing type DIN rail housing

Type Upper part, closed

Max. IP code to attain IP20

Mounting type Snap in

[Back to top](#)Dimensions

Width [w] 25 mm

Height [h] 100 mm

Depth [d] 12 mm

[Back to top](#)Material data

Color (RAL) blue (5015)

Flammability rating according to UL 94 V0

Housing material Polyamide

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

[Back to top](#)Mechanical strength/tumbling barrel

Specification IEC 60068-2-31:2008-05

Height of fall 50 cm

Number of drop cycles 50

[Back to top](#)Thermostability (Ball Thrust Test)

Specification IEC 60695-10-2:2014-02

Temperature 125 °C

Test duration 1 h

Force 20

[Back to top](#)Test for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

[Back...](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-C100X12-5015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.