

INDUSTRIAL COMPONENT DATA

ICS25-C122X12-9005 1072525 PHOENIX CONTACT DIN rail housing, Upper part, closed, width: 25 mm, height: 122 m..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-C122X12-9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-C122X12-9005
Catalog number	1072525
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-80C4663078
Generated	2026-08-05

Product Overview

DIN rail housing, Upper part, closed, width: 25 mm, height: 122 mm, depth: 12 mm, color: black (9005)

Rail box, Top, closed, width: 25 mm, height: 122.5 mm, depth: 14.35 mm, colour: black (Similar RAL 9005)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1072525

Packing unit 1

GTIN 4055626765501

Custom tariff number 85389099

Item properties

Material data

Mechanical strength/tumbling barrel

Test for assessing the risk of fire (glow wire)

General information

Standards and regulations

Dimensions

Ambient conditions

Thermostability (Ball Thrust Test)

Test for substances that would hinder coating with paint or varnish

Packaging information

Classifications

Item properties

Brief article description Upper part of housing

Type ICS25-C122X12-9005

Order No. 1072525

Housing type DIN rail housing

Type Upper part, closed

Max. IP code to attain IP20

Mounting type Snap in

Back to topDimensions

Width [w] 25 mm

Height [h] 122 mm

Depth [d] 12 mm

Back to topMaterial data

Color (RAL) black (9005)

Flammability rating according to UL 94 V0

Housing material Polyamide

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

Back to topMechanical strength/tumbling barrel

Specification IEC 60068-2-31:2008-05

Height of fall 50 cm

Number of drop cycles 50

Back to topThermostability (Ball Thrust Test)

Specification IEC 60695-10-2:2014-02

Temperature 125 °C

Test duration 1 h

Force 20

Back to topTest for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Bac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-C122X12-9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.