

INDUSTRIAL COMPONENT DATA

ICS25-C77X12-7035 1019703 PHOENIX CONTACT Upper part of housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-C77X12-7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-C77X12-7035
Catalog number	1019703
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-C03D8070C9
Generated	2026-08-05

Product Overview

Upper part of housing

Rail box, Top, closed, width: 25 mm, height: 77.5 mm, depth: 14.35 mm, colour: light grey (7035)

DIN rail control box, top, closed, width: 25 mm, height: 77.5 mm, depth: 14.35 mm, colour: light grey (similar to RAL 7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Housing (HS)**

Additional Product Information

Key Commercial Data

Orderkey 1019703

Packing unit 10 pc

Minimum order quantity 10 pc

GTIN 4055626507248

Weight per Piece (excluding packing) 8.500 g

Custom tariff number 85389099

Country of origin DE (Germany)

Item properties

Brief article description Upper part of housing

Type ICS25-C77X12-7035

Order No. 1019703

Housing type Component housing

Type Upper part

Dimensions

Width [w] 25 mm

Height [h] 77 mm

Depth [d] 12 mm

Material data

Housing material PA 6.6

Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 70 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 100 °C (observe derating)

Mechanical strength/tumbling barrel

Height of fall 50 cm

Number of drop cycles 50

Thermostability (Ball Thrust Test)

Specification IEC 60695-10-2:2014-02

Temperature 125 °C

Test duration 1 h

Force 20

Test for assessing the risk of fire (glow wire)

Specification IEC 60695-2-11:2014-02

Temperature 850 °C

Time of exposure 30 s

Test for substances that would hinder coating with paint or varnish

Specification VW PV 3.10.7:2005-02

Packaging information

Pieces per package 10

Denomination packing units Pcs.

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127180505eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 5.0EC001031ETIM 6.0EC001031

ETIM for 1019703 Low-voltage industrial controls...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-C77X12-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.