

INDUSTRIAL COMPONENT DATA

ICS25-F22J-9005 1072501 PHOENIX CONTACT DIN rail housing, ICS filler, with RJ45 function cutout, width: 25 m..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-F22J-9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-F22J-9005
Catalog number	1072501
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-BF1D026DC5
Generated	2026-08-04

Product Overview

DIN rail housing, ICS filler, with RJ45 function cutout, width: 25 mm, height: 7 mm, depth: 22.5 mm, color: black (9005)

Rail Housing, ICS Plug, with Open Section for RJ45, Width: 25mm, Height: 7.25mm, Depth: 22.4mm, Color: Black (9005)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1072501

Packing unit 1

GTIN 4055626765129

Custom tariff number 85389099

Item properties

Material data

General information

Standards and regulations

Dimensions

Ambient conditions

Packaging information

Classifications

Item properties

Brief article description Connection plate

Type ICS25-F22J-9005

Order No. 1072501

Housing type DIN rail housing

Housing series ICS

Type ICS filler, with RJ45 function cutout

Mounting type Slot

Ventilation openings present no

[Back to top](#)Dimensions

Width [w] 25 mm

Height [h] 7 mm

Depth [d] 22.5 mm

[Back to top](#)Material data

Color (RAL) black (9005)

Flammability rating according to UL 94 V0

Housing material Polyamide

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

[Back to top](#)General information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

[Back to top](#)Packaging information

Pieces per package 10

Denomination packing units Pcs.

Outer packaging type Resealable bag

[Back to top](#)Standards and regulations

Flammability rating according to UL 94 V0

[Back to top](#)Classifications

eCl@ss

eCl@ss 5.1 27180506

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to top](#)ETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

[Back to top](#)

ETIM f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-F22J-9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.