

INDUSTRIAL COMPONENT DATA

ICS25-F45S-5015 1071767 PHOENIX CONTACT DIN rail housing, ICS filler, closed, width: 25 mm, height: 7 mm, de..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-F45S-5015



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-F45S-5015
Catalog number	1071767
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-5E61A401FA
Generated	2026-08-06

Product Overview

DIN rail housing, ICS filler, closed, width: 25 mm, height: 7 mm, depth: 45 mm, color: blue (5015)

Rail box, ICS plug, closed, width: 25 mm, height: 7.25 mm, depth: 44.9 mm, colour: blue (Similar RAL 5015)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1071767

Packing unit 1

GTIN 4055626759937

Custom tariff number 39269097

Item properties

Material data

General information

Standards and regulations

Dimensions

Ambient conditions

Packaging information

Classifications

Item properties

Brief article description Connection plate

Type ICS25-F45S-5015

Order No. 1071767

Housing type DIN rail housing

Housing series ICS

Type ICS filler, closed

Mounting type Slot

Ventilation openings present no

Back to topDimensions

Width [w] 25 mm

Height [h] 7 mm

Depth [d] 45 mm

Back to topMaterial data

Color (RAL) blue (5015)

Flammability rating according to UL 94 V0

Housing material Polyamide

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

Back to topGeneral information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

Back to topPackaging information

Pieces per package 10

Denomination packing units Pcs.

Outer packaging type Resealable bag

Back to topStandards and regulations

Flammability rating according to UL 94 V0

Back to topClassifications

eCI@ss

eCI@ss 8.0 27182702

eCI@ss 9.0 27182702

Back to topETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC001031

Back to top

ETIM for 1071767 Low-voltage industrial controls and switchgear (EC002779)

Feature Name....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-F45S-5015 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.