

INDUSTRIAL COMPONENT DATA

ICS25-F45V-7035 1079492 PHOENIX CONTACT DIN rail housing, ICS filler, with vents, width: 25 mm, height: 7 mm..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-F45V-7035



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-F45V-7035
Catalog number	1079492
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-4AAD98FB9D
Generated	2026-08-06

Product Overview

DIN rail housing, ICS filler, with vents, width: 25 mm, height: 7 mm, depth: 45 mm, color: light gray (7035)
Rail box, ICS plug, with ventilation slits, width: 25 mm, height: 7.25 mm, depth: 44.9 mm, colour: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Housing (HS)

Additional Product Information

Key Commercial Data
Orderkey 1079492
Packing unit 1 pc
Minimum order quantity 10 pc
GTIN 4055626798691
Weight per Piece (excluding packing) 2.000 g
Custom tariff number 85389099
Country of origin PL (Poland)
Item properties
Material data
General information
Standards and regulations
Dimensions
Ambient conditions

Packaging information

Classifications

Item properties

Brief article description Connection plate

Type ICS25-F45V-7035

Order No. 1079492

Housing type DIN rail housing

Housing series ICS

Type ICS filler, with vents

Mounting type Slot

Ventilation openings present yes

Back to topDimensions

Width [w] 25 mm

Height [h] 7 mm

Depth [d] 45 mm

Back to topMaterial data

Color (RAL) light gray (7035)

Flammability rating according to UL 94 V0

Housing material Polyamide

Back to topAmbient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

Back to topGeneral information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

Back to topPackaging information

Pieces per package 10

Denomination packing units Pcs.

Outer packaging type Resealable bag

Back to topStandards and regulations

Flammability rating according to UL 94 V0

Back to topClassifications

eCl@ss

eCl@ss 5.1 27180506

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-F45V-7035 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.