

INDUSTRIAL COMPONENT DATA

ICS25-KIT-BC122X110-V-7035+4PPC4 1342872 PHOENIX CONTACT Rail housing, for DIN rail mounting, with closed sn..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-KIT-BC122X110-V-7035+4PPC4



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-KIT-BC122X110-V-7035+4PPC4
Catalog number	1342872
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-CD2CC6A94E
Generated	2026-08-06

Product Overview

Rail housing, for DIN rail mounting, with closed snap-in lid, colour: light grey (Similar RAL 7035), width: 25 mm, height: 122.5 mm, depth: 116.7 mm, incl. 4 pcs PCB connectors, 4 poles, push-in spring connection, for 2.5 mm², nominal current: 16 A, 320 V, PCB surface: 11900 mm²

Rail housing, for DIN rail mounting, with closed snap-on lid, colour: luminous grey (7035), width: 25 mm, height: 122.5 mm, depth: 116.7 mm, incl. 4 PCB connector units, 4 poles, push-in spring-loaded connection, for 2.5 mm², rated current: 16 A, 320 V, printed circuit board surface: 11900 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT
--------------	-----------------

Additional Product Information

Technical dataNotesGeneral Please note the assembly instructions in the download area.

General Contact Pad Material for Galvanic Bus Connectors Gold (Hard Gold)

General The indication of the surface of the printed circuit board is indicative and refers to a basic printed circuit board. The enclosure can also accommodate multiple printed circuit boards.

Item PropertiesProduct Type Shell Set

Product Family ICS25

Number of poles 16

Max. number of poles 16 (pitch: 5 mm)

Number of rows 4

Execution for DIN rail mounting, with closed snap-on lid

incl. 4 PCB connector units, 4-pole, Push-in spring-loaded connection, for 2.5 mm², rated current: 16 A, 320 V

Type of housing Lane box

Available ventilation hole Yes

Housing Series .ICS

Connection dataConnection type Push-in spring connection

DimensionsDimension Scheme

Width 25 mm

Height 122.5 mm

Depth 116.7 mm

Depth from the top edge of the DIN rail 110 mm

Printed circuit board design

Printed Circuit Board Thickness 1.4 mm ... 1.8 mm

Material DataColour Luminous Grey (7035)

Flammability class according to UL 94 V0

Surface Characteristics Not Treated

Shell material Polyamide

Environmental and life-life conditionsEnvironmental conditions

Maximum achievable IP code IP20

Ambient Temperature (Service) -40 °C ... 105 °C (depending on dissipation)

Ambient Temperature (Storage/Transport) -40 °C ... 55 °C

Ambient Temperature (Mounting) -5 °C ... 100 °C

Relative humidity of the air (storage/transport) 80% (maximum)

Printed Circuit Board DataNumber....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-KIT-BC122X110-V-7035+4PPC4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.