

INDUSTRIAL COMPONENT DATA

ICS25-KIT-BC122X110-V-7035+4PSC4 1342851 PHOENIX CONTACT Rail housing, for DIN rail mounting, with closed sn..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-KIT-BC122X110-V-7035+4PSC4



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-KIT-BC122X110-V-7035+4PSC4
Catalog number	1342851
Category	Electronic enclosure
Minimum order	1 Pcs
Document ID	EO-5B83E39321
Generated	2026-08-06

Product Overview

Rail housing, for DIN rail mounting, with closed snap-in lid, colour: light grey (Similar RAL 7035), width: 25 mm, height: 122.5 mm, depth: 116.7 mm, incl. 4 pcs PCB connectors, 4 poles, screw connection, for 2.5 mm², nominal current: 16 A, 320 V, PCB surface: 11900 mm²

DIN rail housing, for mounting on a DIN rail, with closed latching cover, color: light grey (7035), width: 25 mm, height: 122.5 mm, depth: 116.7 mm, incl. 4 PCB connectors, 4-pos., screw connection, for 2.5 mm², nominal current: 16 A, 320 V, PCB surface: 11900 mm²

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT
--------------	-----------------

Additional Product Information

Technical dataNotesGeneral Please observe the assembly instructions available in the download area.

General Material of contact pads for bus connector, galvanic gold (hard gold)

General The PCB surface specification is for orientation purposes and is based on a basic PCB. The housing can also accommodate several PCBs.

Product propertiesProduct type Stackable housing set

Product family ICS25

Number of positions 16

Max. number of positions 16 (pitch: 5 mm)

Number of rows 4

Type for mounting on a DIN rail, with closed latching cover

incl. 4 PCB connectors, 4-pos., screw connection, for 2.5 mm², nominal current: 16 A, 320 V

Housing type DIN rail housing

Ventilation openings present yes

Housing series ICS

Connection dataConnection method Screw connection with tension sleeve

DimensionsDimensional drawing

Width 25 mm

Height 122.5 mm

Depth 116.7 mm

Depth from top edge of DIN rail 110 mm

PCB design

PCB thickness 1.4 mm ... 1.8 mm

Material specificationsColor light grey (7035)

Flammability rating according to UL 94 V0

Surface characteristics untreated

Housing material Polyamide

Environmental and real-life conditionsAmbient conditions

Max. IP code to attain IP20

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Relative humidity (storage/transport) 80 % (maximum)

PCB dataNumber of PCB holders 2

Type of PCB mount Latching

Total PCB surface 11900 mm²

T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-KIT-BC122X110-V-7035+4PSC4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.