

INDUSTRIAL COMPONENT DATA

ICS25-TL100X12-9005 1072528 PHOENIX CONTACT DIN rail housing, Upper part, with transparent hinged cover, wid..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-TL100X12-9005



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS25-TL100X12-9005
Catalog number	1072528
Category	Extruded profile modular housing
Minimum order	10 Pcs
Document ID	EO-25B626B467
Generated	2026-08-05

Product Overview

DIN rail housing, Upper part, with transparent hinged cover, width: 25 mm, height: 100 mm, depth: 12 mm, color: black (9005)

Rail box, Top, with transparent hinged lid, width: 25 mm, height: 101 mm, depth: 14.35 mm, colour: black (Similar RAL 9005)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1072528

Packing unit 1

GTIN 4055626765235

Custom tariff number 85389099

Item properties

Material data

General information

Standards and regulations

Dimensions

Ambient conditions

Packaging information

Classifications

Item properties

Brief article description Upper part of housing

Type ICS25-TL100X12-9005

Order No. 1072528

Housing type DIN rail housing

Type Upper part, with transparent hinged cover

Max. IP code to attain IP20

Mounting type Snap in

[Back to top](#)Dimensions

Width [w] 25 mm

Height [h] 100 mm

Depth [d] 12 mm

[Back to top](#)Material data

Color (RAL) black (9005)

Flammability rating according to UL 94 V0

Housing material Polyamide

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

[Back to top](#)General information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

[Back to top](#)Packaging information

Type of packaging packed in cardboard

Pieces per package 10

Denomination packing units Pcs.

Outer packaging type Carton

[Back to top](#)Standards and regulations

Flammability rating according to UL 94 V0

[Back to top](#)Classifications

eCl@ss

eCl@ss 5.1 27180505

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to top](#)ETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC00...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-TL100X12-9005 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.