

## INDUSTRIAL COMPONENT DATA

# ICS25-TL100X12-9005 1072528 PHOENIX CONTACT DIN rail housing, Upper part, with transparent hinged cover, wid..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS25-TL100X12-9005



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | ICS25-TL100X12-9005              |
| Catalog number  | 1072528                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-25B626B467                    |
| Generated       | 2026-08-06                       |

## Product Overview

DIN rail housing, Upper part, with transparent hinged cover, width: 25 mm, height: 100 mm, depth: 12 mm, color: black (9005)

Rail box, Top, with transparent hinged lid, width: 25 mm, height: 101 mm, depth: 14.35 mm, colour: black (Similar RAL 9005)

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1072528

Packing unit 1

GTIN 4055626765235

Custom tariff number 85389099

Item properties

Material data

General information

Standards and regulations

Dimensions

Ambient conditions

Packaging information

## Classifications

### Item properties

Brief article description Upper part of housing

Type ICS25-TL100X12-9005

Order No. 1072528

Housing type DIN rail housing

Type Upper part, with transparent hinged cover

Max. IP code to attain IP20

Mounting type Snap in

[Back to top](#)Dimensions

Width [ w ] 25 mm

Height [ h ] 100 mm

Depth [ d ] 12 mm

[Back to top](#)Material data

Color (RAL) black (9005)

Flammability rating according to UL 94 V0

Housing material Polyamide

[Back to top](#)Ambient conditions

Ambient temperature (storage/transport) -40 °C ... 55 °C

Ambient temperature (assembly) -5 °C ... 100 °C

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Relative humidity (storage/transport) 80 %

[Back to top](#)General information

Type of note Assembly instruction:

Note Refer to the data sheet for the range in the download area.

[Back to top](#)Packaging information

Type of packaging packed in cardboard

Pieces per package 10

Denomination packing units Pcs.

Outer packaging type Carton

[Back to top](#)Standards and regulations

Flammability rating according to UL 94 V0

[Back to top](#)Classifications

eCl@ss

eCl@ss 5.1 27180505

eCl@ss 6.0 27180800

eCl@ss 7.0 27182702

eCl@ss 8.0 27182702

eCl@ss 9.0 27182702

[Back to top](#)ETIM

ETIM 5.0 EC001031

ETIM 6.0 EC001031

ETIM 7.0 EC00...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS25-TL100X12-9005 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.