

INDUSTRIAL COMPONENT DATA

ICS50-C122X12-D2,4-TRG-7035 VPE1 1525286 PHOENIX CONTACT Rail box, Top, integrated resistive 2.4" touchscreen..

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICS50-C122X12-D2,4-TRG-7035 VPE1



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICS50-C122X12-D2,4-TRG-7035 VPE1
Catalog number	1525286
Category	Extruded profile modular housing
Minimum order	1 Pcs
Document ID	EO-6112B9F72C
Generated	2026-08-05

Product Overview

Rail box, Top, integrated resistive 2.4" touchscreen, interface: 4-wire SPI half duplex, width: 50.1 mm, height: 122.5 mm, depth: 14.35 mm

Rail box, Top, closed

DIN rail housing, Upper part, integrated 2.4" resistive touch display, interface: 4-wire SPI half duplex, width: 50.1 mm, height: 122.5 mm, depth: 14.35 mm, color: light grey (7035)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Housing (HS)
--------------	--------------------------------

Additional Product Information

Technical dataNotesGeneral Refer to the data sheet for the range in the download area.

Product propertiesProduct type Upper housing part

Product family ICS50-...122X..

Type Upper part, integrated 2.4" resistive touch display

Housing type DIN rail housing

Ventilation openings present no

Housing series ICS

Display

Display type Color display TFT

Diagonal (Display)

2.4 in. / 6.9 cm (Display)

Display formats 3:4
Display lighting type LED, white
Controller ST7789V
Connection data Cross section AWG (converted acc. to IEC)
Interfaces Interface 4-wire SPI half duplex
Dimensions Dimensional drawing
Width 50.1 mm
Height 122.5 mm
Depth 14.35 mm
Dimensions 50.1 mm x 100 mm x 14.35 mm
48.96 mm x 36.72 mm (Active range)
PCB design
PCB thickness 1.4 mm ... 1.8 mm
Material specifications Color light grey (7035)
Flammability rating according to UL 94 V0
CTI according to IEC 60112 600
Surface characteristics untreated
Housing material Polyamide
Environmental and real-life conditions Vibration test
Specification IEC 60068-2-6:2007-12
Result Test passed
Frequency 10 - 150 - 10 Hz
Sweep speed 1 octave/min
Amplitude 0.15 mm (10 Hz ... 58.1 Hz)
Acceleration 20 m/s²
Test duration per axis 2.5 h
Test directions X-, Y- and Z-axis
Shocks
Specification IEC 60068-2-27:2008-02
Result Test passed
Acceleration 150 m/s²
Shock duration 11 ms
Number of shocks per direction 3
Test directions X-, Y- and Z-axis (pos. and neg.)
Test for substances that would hinder coating with paint or varnish
Specification VDMA 24364:...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICS50-C122X12-D2,4-TRG-7035 VPE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.