

INDUSTRIAL COMPONENT DATA

ICV 2,5/ 2-G-5,08 BK 1701454 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: ICV 2,5/ 2-G-5,08 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	ICV 2,5/ 2-G-5,08 BK
Catalog number	1701454
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-49A3B3DA72
Generated	2026-08-06

Product Overview

Printed-circuit board connector

Printed circuit board base case, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 2, number of rows: 1, number of poles: 2, number of connections: 2, family of articles: ICV 2.5/.. -G, pitch: 5.08 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 3.6 mm, number of solder pins per potential: 2, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1701454

Packing unit 1

GTIN 4046356536028

Custom tariff number 85366930

Dimensions

Length [l] 10.2 mm

Width 12.16 mm

Pitch 5.08 mm

Dimension a 5.08 mm

Width [w] 12.16 mm

Height [h] 22.5 mm

Height 18.9 mm

Length of the solder pin 3.6 mm

Pin dimensions 0.47 x 1.15 mm

Length 10.2 mm

General

Range of articles ICV 2,5/..-G

Rated voltage (III/3) 320 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Color black

Number of positions 2

Standards and Regulations

Connection in acc. with standard EN-VDE

CSA

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ICV 2,5/ 2-G-5,08 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.