

INDUSTRIAL COMPONENT DATA

IMC 1,5/10-ST-3,81AUBKBDWH1-10 1704625 PHOENIX CONTACT Plug-in part, rated current: 8 A, number of poles: 10..

Brand: PHOENIX CONTACT | Manufacturer Part Number: IMC 1,5/10-ST-3,81AUBKBDWH1-10



Manufacturer	PHOENIX CONTACT
MPN / Reference	IMC 1,5/10-ST-3,81AUBKBDWH1-10
Catalog number	1704625
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-28BC79652E
Generated	2026-08-06

Product Overview

Plug-in part, rated current: 8 A, number of poles: 10, pitch: 3.81 mm, connection type: Screw connection with traction capsule, color: black, contact surface: Gold

Connector for printed circuit board, nominal section: 1.5 mm², color: black, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Gold, contact type: Male, number of potentials: 10, number of rows: 1, number of poles: 10, number of connections: 10, family of articles: BMI 1.5/..-ST, pitch: 3.81 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor/printed circuit board connection direction: 0 °, plug-in system: COMBICON MC 1.5, lock: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Plug component, nominal current: 8 A, number of positions: 10, pitch: 3.81 mm, connection method: Screw connection with tension sleeve, color: black, contact surface: Gold

Your advantages

Gold-plated contacts ensure transfer quality remains stable over the long termWell-known connection principle allows worldwide useLow temperature rise, thanks to maximum contact forceInverted connector with pin contacts for touch-proof device outputs or free-hanging cable/cable connectionsAllows connection of two conductorsKey Commercial Data
Orderkey 1704625

Packing unit 1

GTIN 4046356730815

Custom tariff number 85366990

General

Range of articles IMC 1,5/..-ST

Type of contact Male connector

Number of positions 10

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 160 V

Connection in acc. with standard EN-VDE

Nominal current IN 8 A

Nominal cross section 1.5 mm²

Connection data

Conductor cross section solid min. 0.14 mm²

Conductor cross section solid max. 1.5 mm²

Conductor cross section flexible min. 0.14 mm²

Conductor cross section flexible max. 1.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 0.5 mm²

Conductor cross section AWG min. 28

Conductor cross section AWG max. 16

2 conductors with s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IMC 1,5/10-ST-3,81AUBKBDWH1-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.