

INDUSTRIAL COMPONENT DATA

FKC 2,5/ 4-ST-5,08 BKBDWH-GND 1834504 PHOENIX CONTACT PCB connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FKC 2,5/ 4-ST-5,08 BKBDWH-GND



Manufacturer	PHOENIX CONTACT
MPN / Reference	FKC 2,5/ 4-ST-5,08 BKBDWH-GND
Catalog number	1834504
Category	Cable connector
Minimum order	1000 Pcs
Document ID	EO-62B1FD407F
Generated	2026-08-05

Product Overview

PCB connector

PCB connector, nominal cross-section: 2.5 mm², colour: black, nominal current: 12 A, nominal voltage (III/2): 320 V, surface contacts: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, article family: FKC 2.5/.. -ST, pitch: 5.08mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, attachment type: without, packing type: boxed packaging

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1834504

Packing unit 1

GTIN 4046356991186

Custom tariff number 85366990

Dimensions

Length [l] 25.73 mm

Width [w] 20.94 mm

Height [h] 15 mm

Pitch 5.08 mm

Dimension a 15.24 mm

General

Range of articles FKC 2,5/...-ST

Number of positions 4

Connection method Push-in spring connection

Rated surge voltage (III/3) 4 kV

Rated surge voltage (III/2) 4 kV

Rated surge voltage (II/2) 4 kV

Rated voltage (III/3) 320 V

Rated voltage (III/2) 320 V

Rated voltage (II/2) 630 V

Connection in acc. with standard EN-VDE

Nominal current I_N 12 A

Nominal cross section 2.5 mm²

Internal cylindrical gage A2

Stripping length 10 mm

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 2.5 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²

2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. 1.5 mm²

Standards and Regulations

Connection in acc. with standard EN-VDE

Envir...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FKC 2,5/ 4-ST-5,08 BKBDWH-GND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.