


INDUSTRIAL COMPONENT DATA

ZFKKDSA 1,5C-5,0-11 1710128 PHOENIX CONTACT PCB terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: ZFKKDSA 1,5C-5,0-11



Manufacturer	PHOENIX CONTACT
MPN / Reference	ZFKKDSA 1,5C-5,0-11
Catalog number	1710128
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-DB219BAF22
Generated	2026-08-06

Product Overview

PCB terminal block

Printed circuit board terminal block, rated current: 16 A, rated voltage (III/2): 400 V, rated cross-section: 1.5 mm², number of potentials: 22, number of rows: 2, number of poles per row: 11, article family: ZFKKDS(A) 1.5C, pitch: 5 mm, connection type: Spring connection, mounting: Wave soldering, conductor connection direction/printed circuit board: 45 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.7 mm, number of solder pins per potential: 1, packaging type: boxed. The item can be aligned with different numbers of poles!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

Additional Product Information

Key Commercial Data

Orderkey 1710128

Packing unit 1

GTIN 4055626134123

Custom tariff number 85369010

Dimensions

Length [l] 21 mm

Pitch 5 mm

Dimension a 50 mm

Width [w] 55 mm

Height 26 mm

Height [h] 29.7 mm

Solder pin [P] 3.7 mm

Hole diameter 1.1 mm

General

Range of articles ZFKKDS(A) 1,5C

Insulating material group I

Rated voltage (III/2) 400 V

Nominal current IN 16 A

Nominal cross section 1.5 mm²

Solder pin surface

Flammability rating according to UL 94 V0

Number of positions 11

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss 7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 13.239121432

ETIM for 1710128 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

29.7 mm

Number of electrical connections (EF008252)

22

Number of levels (EF002659)

2

Modular spacing connections (EF006827)

5 mm

Rated current In (EF008250)

16 A

Rated voltage (EF000228)

400 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Spring clamp connection

Connectable conductor cross section solid-core (EF007337)

0.2 mm²

Connectable conductor cross section fine-strand with cable end sleeve (EF007339)

0.25 mm²

Connectable conductor cross section f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ZFKKDSA 1,5C-5,0-11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.