

INDUSTRIAL COMPONENT DATA

INJ 2111-T 2703013 PHOENIX CONTACT Injector

Brand: PHOENIX CONTACT | Manufacturer Part Number: INJ 2111-T



Manufacturer	PHOENIX CONTACT
MPN / Reference	INJ 2111-T
Catalog number	2703013
Category	Patch panel copper (twisted pair)
Minimum order	1 Pcs
Document ID	EO-4962786DA9
Generated	2026-07-31

Product Overview

Injector

PoE injector, 60 W, RJ45 female connector on screw terminals, 10/100/1000 MBit/s, rail mounting, IP20, potential separation, protective contact with traction compensation, shielding current monitoring, surge protection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Safety

Additional Product Information

Key Commercial Data

Orderkey 2703013

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626463216

Weight per Piece (excluding packing) 324.720 g

Custom tariff number 85176200

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Dimensional drawing

Width 30.2 mm

Height 130 mm

Depth 120 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 75 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Altitude 5000 m (For restrictions see manufacturer's declaration)

Degree of protection IP20 (Manufacturer's declaration)

General

Electrical isolation VCC // SCM + FE // PoE

Test voltage data interface/power supply 1.5 kV AC (50 Hz, 1 min.)

Standards/regulations IEC 61643-21

Electromagnetic compatibility Conformance with EMC Directive 2014/30/EU

Mounting position vertical

Net weight 324.72 g

Housing material Plastic

Color gray

MTTF 1797 Years (SN 29500 standard, temperature 25 °C, operating cycle 21 % (5 days a week, 8 hours a day))

733 Years (SN 29500 standard, temperature 40 °C, operating cycle 34.25 % (5 days a week, 12 hours a day))

283 Years (SN 29500 standard, temperature 40 °C, operating cycle 100 % (7 days a week, 24 hours a day))

Conformance CE-compliant

UL, USA UL 60079-0 Ed. 6 / UL 60079-15 Ed. 4

UL, USA/Canada Class I, Zone 2, AEx nA IIC T4, Ex nA IIC Gc X T4

Class I, Division 2, Groups A, B,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / INJ 2111-T with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.