

INDUSTRIAL COMPONENT DATA

IB IL AI 2-HART-PAC 2862149 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL AI 2-HART-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL AI 2-HART-PAC
Catalog number	2862149
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-AF3FEE8E4D
Generated	2026-08-01

Product Overview

Inline terminal

Inline, Analog Input Module, Analog Inputs: 2, 4 mA ... 20 mA, 0 mA... 25 mA, connection technology: 2 conductors, transmission rate on the local bus: 500 kBit/s, HART - Functionality, HART protocol transmission, protection rating: IP20, including inline connectors and marking fields

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2862149

Packing unit 1 pc

Catalog page Page 161 (C-6-2017)

GTIN 4017918918835

Weight per Piece (excluding packing) 134.000 g

Custom tariff number 85389091

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Dimensional drawing

Width 48.8 mm

Height 135 mm

Depth 71.5 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

General

Mounting type DIN rail

Net weight 134 g

Operating mode Process data operation with 2 words, PCP with 2 words

Diagnostics messages Failure of the internal I/O supply Yes

Peripheral fault Error message in the process data

User error Error message in the process data

Interfaces

Designation Inline local bus

No. of channels 2

Connection method Inline data jumper

Transmission speed 500 kbps

Transmission physics Copper

Inline potentials

Designation Communications power (UL)

Supply voltage 7.5 V DC (via voltage jumper)

Current consumption typ. 95 mA

max. 110 mA

Designation Supply of analog modules (UANA)

Supply voltage 24 V DC

Supply voltage range 19.2 V DC ... 30 V DC (including all tolerances, including ripple)

Current cons...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL AI 2-HART-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.