

INDUSTRIAL COMPONENT DATA

IB IL TEMP 2 RTD-PAC 2861328 PHOENIX CONTACT Inline function terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL TEMP 2 RTD-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL TEMP 2 RTD-PAC
Catalog number	2861328
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-787188ADBA
Generated	2026-07-29

Product Overview

Inline function terminal

Inline, Temperature recording module, Analogue RTD inputs: 2, connection technology: 2, 3, 4 conductors, transmission speed on local bus: 500 kBit/s, protection rating: IP20, including Inline connector and marking surface

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > I/O**

Additional Product Information

Key Commercial Data

Orderkey 2861328

Packing unit 1 pc

Catalog page Page 165 (C-6-2017)

GTIN 4017918894269

Weight per Piece (excluding packing) 67.000 g

Custom tariff number 85389091

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Dimensional drawing

Width 12.2 mm

Height 136.8 mm

Depth 71.5 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 10 % ... 95 % (non-condensing)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

80 kPa ... 106 kPa (up to 3000 m above sea level, in ATEX Zone 2)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

General

Mounting type DIN rail

Net weight 67 g

Note on weight specifications with connector

Operating mode Process data operation with 2 words

Diagnostics messages Failure of the internal I/O supply I/O error message sent to the bus coupler

Failure of or insufficient communications power ULI/O error message sent to the bus coupler

Peripheral fault Error message in the process data

User error Error message in the process data

Interfaces

Designation Inline local bus

No. of channels 2

Connection method Inline data jumper

Transmission speed 500 kbps

Inline potentials

Designation Communications...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL TEMP 2 RTD-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.