


INDUSTRIAL COMPONENT DATA

IB IL CNT-PAC 2861852 PHOENIX CONTACT Inline function terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL CNT-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL CNT-PAC
Catalog number	2861852
Category	Fieldbus, decentr. periphery - function-/technology module
Minimum order	1 Pcs
Document ID	EO-7E645DAF7D
Generated	2026-07-31

Product Overview

Inline function terminal

Inline counter terminal block, complete with accessories (connectors and marking surfaces), 1 meter input, 1 control input, 1 output, 24 V DC, 500 mA, 3-conductor connection technology

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Technical dataDimensionsDimensional drawing

Width 24.4 mm

Height 135 mm

Depth 71.5 mm

NotesNote on application

Note on application Only for industrial use

InterfacesInline local bus

Number of interfaces 2

Connection method Inline data jumper

Transmission speed 500 kbps

Transmission physics Copper

System propertiesModule

ID code (dec.) 191

ID code (hex) BF
Length code (hex) 02
Length code (dec) 02
Process data channel 32 bit
Input address area 4 Byte
Output address area 4 Byte
Register length 4 Byte
Required parameter data 1 Byte
Required configuration data 5 Byte
Input dataCounter:
Input name Counter input for 24 V signals
Connection method Spring-cage connection
Connection technology 2-, 3-conductor
Number of inputs 1 (only one counter input can be used, either for 24 V or for 5 V signals)
Operating mode Event counting, frequency/time measurement
Input voltage 24 V DC (Nominal voltage)
30 V DC (maximum)
Input voltage range "0" signal 0 V DC ... 5 V DC
Input voltage range "1" signal 15 V DC ... 30 V DC
Input frequency max. 100 kHz
Input current typ. 5 mA
Input resistance approx. 5.7 k Ω
Counter:
Input name Counter input for 5 V signals
Connection method Spring-cage connection
Connection technology 2-conductor (shielded), external 5 V supply
Number of inputs 1 (only one counter input can be used, either for 24 V or for 5 V signals)
Operating mode Event counting, frequency/time measurement
Input voltage 5 V DC (Nominal voltage)
8 V DC (maximum)
Input voltage range "0" signal 0....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL CNT-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.