

INDUSTRIAL COMPONENT DATA

IB IL 24 DO 4-XC-PAC 2701155 PHOENIX CONTACT Inline terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL 24 DO 4-XC-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL 24 DO 4-XC-PAC
Catalog number	2701155
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-693BB24B58
Generated	2026-08-03

Product Overview

Inline terminal

Inline, Digital output module, Digital outputs:4, 24 VDC, connection technology:3 conductors, Extreme Condition variant, transmission speed on the local bus:500 kBit/s, protection index: IP20, including Inline connector and marking surface

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data

Orderkey 2701155

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 152 (C-6-2017)

GTIN 4046356713818

Weight per Piece (excluding packing) 66.000 g

Custom tariff number 85389091

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Dimensional drawing

Width 12.2 mm

Height 140.5 mm

Depth 71.5 mm

Note on dimensions Housing dimensions

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C (Standard)

-40 °C ... 70 °C (Extended, see section "Tested successfully: use under extreme ambient conditions" in the data sheet.)

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 10 % ... 95 % (according to DIN EN 61131-2)

Permissible humidity (storage/transport) 10 % ... 95 % (according to DIN EN 61131-2)

Air pressure (operation) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Air pressure (storage/transport) 70 kPa ... 106 kPa (up to 3000 m above sea level)

Degree of protection IP20

General

Mounting type DIN rail

Net weight 66 g

Note on weight specifications with connector

Operating mode Process data operation with 4 bits

Diagnostics messages Short-circuit / overload of the digital outputs Error message in the diagnostic code (bus) and display (2 Hz) via the LED (D) on the module

Interfaces

Designation Inline local bus

No. of channels 2

Connection method Inline data jumper

Transmission speed 500 kbps

Inline potentials

Designation Communications power (UL)

Supply voltage 7.5 V....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL 24 DO 4-XC-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.