


INDUSTRIAL COMPONENT DATA

IB IL RS 485/422-PRO-PAC 2863627 PHOENIX CONTACT Inline function terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: IB IL RS 485/422-PRO-PAC



Manufacturer	PHOENIX CONTACT
MPN / Reference	IB IL RS 485/422-PRO-PAC
Catalog number	2863627
Category	Fieldbus, decentr. periphery - communication module
Minimum order	1 Pcs
Document ID	EO-0D3E7084F6
Generated	2026-08-03

Product Overview

Inline function terminal

Inline, Communication module, transmission rate on the local bus:500 kBit/s, protection index:IP20, including inline connectors and marking fields

Inline, Communication module, RS-485 interface, RS-422: 1 (with alternative operation), Communication via process data, transmission rate on local bus: 500 kBit/s, protection index: IP20, including inline connectors and marking fields

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2863627

Packing unit 1 pc

Catalog page Page 207 (C-8-2015)

GTIN 4017918946920

Weight per Piece (excluding packing) 135.000 g

Custom tariff number 85389091

Country of origin DE (Germany)

Note

Utilization restriction 1

Dimensions

Dimensional drawing

Width 24.4 mm

Height 136.8 mm

Depth 71.5 mm

Connection data

Designation Inline connector

Connection method Spring-cage connection

Conductor cross section solid min. 0.08 mm²Conductor cross section solid max. 1.5 mm²Conductor cross section flexible min. 0.08 mm²Conductor cross section flexible max. 1.5 mm²

Conductor cross section AWG min. 28

Conductor cross section AWG max. 16

Stripping length 8 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 55 °C

Ambient temperature (storage/transport) -25 °C ... 85 °C

Permissible humidity (operation) 75 % ... 85 % (in the range of -25°C ... +55°C, appropriate measures against increased humidity (> 85%) must be taken.)

Permissible humidity (storage/transport) 75 % ... 85 % (Slight temporary condensation may sometimes appear on the housing, e.g. when the terminal block is brought out of a vehicle into an enclosed room.)

Degree of protection IP20

General

Mounting type DIN rail

Net weight 135 g

Interfaces

Designation Inline local bus

Connection method Inline data jumper

Transmission speed 500 kbps

Interface RS-422/-485

Connection method Spring-cage connection

Transmission physics Copper

Data bits 7 or 8

Stop bits 1 or 2

Input buffer 4 kByte

Output buff...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IB IL RS 485/422-PRO-PAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.