

INDUSTRIAL COMPONENT DATA

EB 3-10 0203328 PHOENIX CONTACT Insertion bridge, Number of positions: 3, Color: gray

Brand: PHOENIX CONTACT | Manufacturer Part Number: EB 3-10



Manufacturer	PHOENIX CONTACT
MPN / Reference	EB 3-10
Catalog number	0203328
Category	Cross-connector for terminal block
Minimum order	10 Pcs
Document ID	EO-E4CB072A29
Generated	2026-07-28

Product Overview

Insertion bridge, Number of positions: 3, Color: gray

Bridge comb, pitch: 10 mm, color: grey

Insertion bridge, pitch: 10 mm, number of positions: 3, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Insertion bridge

Number of positions 3

Pitch 10 mm

Data management status

Article revision 00

DimensionsPitch 10 mm

Material specificationsColor gray (RAL 7042)

Material Copper

Flammability rating according to UL 94 V0

Insulating material PA

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -60 °C ... 105 °C

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (storage/transport) 30 % ... 70 %

MountingMounting type Screw mounting

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EB 3-10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.