

INDUSTRIAL COMPONENT DATA

PTI 2,5-L 3213951 PHOENIX CONTACT Installation level terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PTI 2,5-L



Manufacturer	PHOENIX CONTACT
MPN / Reference	PTI 2,5-L
Catalog number	3213951
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-C2A3AD83C3
Generated	2026-07-31

Product Overview

Installation level terminal block

Distribution floor terminal block, nominal voltage: 400 V, nominal current: 24 A, Push-in connection, Dimensioning cross-section: 4 mm², cross-section: 0.14 mm² - 4 mm², installation class: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 3213951

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 87 (C-1-2017)

GTIN 4046356609609

Weight per Piece (excluding packing) 12.870 g

Custom tariff number 85369010

Country of origin DE (Germany)

General

Note Assembly instructions: For secure fastening of the neutral busbar, supports must be set at the beginning and end of each terminal strip as well as every 20 cm on longer terminal strips.

Number of levels 3

Number of connections 2
Potentials 1
Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Maximum load current 30 A (with 4 mm² conductor cross section and 3-pos. terminal block)
24 A (with a 2.5 mm² conductor cross section)
Rated surge voltage 4 kV
6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.77 W (the value is multiplied when connecting multiple levels)
Maximum load current 30 A (with 4 mm² conductor cross section and 3-pos. terminal block)
Nominal current I_N 24 A (with 4 mm² conductor cross section)
Nominal voltage U_N 400 V (phase conductor/phase conductor)
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage set...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PTI 2,5-L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.