

**INDUSTRIAL COMPONENT DATA**

# UTI 16 3073827 PHOENIX CONTACT Installation terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTI 16



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | PHOENIX CONTACT                         |
| MPN / Reference | UTI 16                                  |
| Catalog number  | 3073827                                 |
| Category        | Multi level installation terminal block |
| Minimum order   | 50 Pcs                                  |
| Document ID     | EO-238B4BB002                           |
| Generated       | 2026-07-29                              |

## Product Overview

Installation terminal block

Terminal block, nominal voltage: 400 V, nominal current: 76 A, Screw connection, 1st floor, right-hand connection, Dimensioning cross-section: 16 mm<sup>2</sup>, cross-section: 6 mm<sup>2</sup> - 25 mm<sup>2</sup>, installation class: NS 35/7.5, NS 35/15, colour: grey

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

## Additional Product Information

Key Commercial Data

Orderkey 3073827

Packing unit 50 pc

Catalog page Page 253 (C-1-2017)

GTIN 4046356347242

Weight per Piece (excluding packing) 22.700 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 16 mm<sup>2</sup>

Color gray  
Insulating material PA  
Flammability rating according to UL 94 V2  
Maximum load current 76 A (with 16 mm<sup>2</sup> conductor cross section)  
Rated surge voltage 6 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 2.43 W  
Maximum load current 76 A  
Nominal current I<sub>N</sub> 76 A  
Nominal voltage U<sub>N</sub> 400 V  
Open side panel No  
Shock protection test specification IEC 60529:2001-02  
Back of the hand protection guaranteed  
Finger protection guaranteed  
Result of surge voltage test Test passed  
Surge voltage test setpoint 7.3 kV  
Result of power-frequency withstand voltage test Test passed  
Power frequency withstand voltage setpoint 1.89 kV  
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed  
Result of bending test Test passed  
Bending test rotation speed 10 rpm  
Bending test turns 135  
Bending test conductor cross section/weight 6 mm<sup>2</sup>/ 1.4 kg  
16 mm<sup>2</sup> / 2.9 kg  
25 mm<sup>2</sup> / 4.5 kg  
Tensile test result Test passed  
Conductor cross section tensile test 6 mm<sup>2</sup>  
Tractive force setpoint 80 N  
Conductor cross section tensile test 16 mm<sup>2</sup>  
Tractive force setpoint 100 N  
Conductor cross section tensile...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTI 16 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.