

INDUSTRIAL COMPONENT DATA

UTI 16 BU 3075728 PHOENIX CONTACT Installation terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTI 16 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTI 16 BU
Catalog number	3075728
Category	Multi level installation terminal block
Minimum order	50 Pcs
Document ID	EO-1E2693750E
Generated	2026-07-29

Product Overview

Installation terminal block

Terminal block, nominal voltage: 400 V, nominal current: 76 A, Screw connection, 1st floor, right-hand connection, Dimensioning cross-section: 16 mm², cross-section: 6 mm² - 25 mm², installation type: NS 35/7.5, NS 35/15, colour: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 3075728

Packing unit 50 pc

Catalog page Page 253 (C-1-2017)

GTIN 4046356518031

Weight per Piece (excluding packing) 27.550 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 16 mm²

Color blue
Insulating material PA
Flammability rating according to UL 94 V2
Maximum load current 76 A (with 16 mm² conductor cross section)
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 2.43 W
Maximum load current 76 A
Nominal current I_N 76 A
Nominal voltage U_N 400 V
Open side panel No
Shock protection test specification IEC 60529:2001-02
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 6 mm²/ 1.4 kg
16 mm² / 2.9 kg
25 mm² / 4.5 kg
Tensile test result Test passed
Conductor cross section tensile test 6 mm²
Tractive force setpoint 80 N
Conductor cross section tensile test 16 mm²
Tractive force setpoint 100 N
Conductor cross section tensile...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTI 16 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.