


INDUSTRIAL COMPONENT DATA

UTI 35 3074088 PHOENIX CONTACT Installation terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTI 35



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTI 35
Catalog number	3074088
Category	Multi level installation terminal block
Minimum order	1 Pcs
Document ID	EO-0467715BBF
Generated	2026-08-03

Product Overview

Installation terminal block

Terminal block, nominal voltage: 800 V, nominal current: 125 A, Screw connection, Dimensioning cross-section: 35 mm², cross-section: 0.75 mm² - 35 mm², installation type: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Modular TBs**

Additional Product Information

Key Commercial Data

Orderkey 3074088

Packing unit 50 pc

Catalog page Page 255 (C-1-2017)

GTIN 4046356347266

Weight per Piece (excluding packing) 44.260 g

Custom tariff number 85369010

Country of origin CN (China)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 35 mm²

Color gray
Insulating material PA
Flammability rating according to UL 94 V2
Maximum load current 125 A (with 35 mm² conductor cross section)
Rated surge voltage 8 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 4.06 W
Maximum load current 125 A (with 35 mm² conductor cross section)
Nominal current I_N 125 A
Nominal voltage U_N 800 V
Open side panel No
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 9.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 3.5 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.75 mm² / 0.4 kg
35 mm² / 6.8 kg
Tensile test result Test passed
Conductor cross section tensile test 0.75 mm²
Tractive force setpoint 30 N
Conductor cross section tensile test 35 mm²
Tractive for...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTI 35 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.