


INDUSTRIAL COMPONENT DATA

FLKM-2FLK14/KDS3-MT/PPA/S7 2295062 PHOENIX CONTACT

Passive module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLKM-2FLK14/KDS3-MT/PPA/S7



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLKM-2FLK14/KDS3-MT/PPA/S7
Catalog number	2295062
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-582F1384AE
Generated	2026-07-31

Product Overview

Passive module

VARIOFACE interconnect module for Siemens SIMATIC® S7-300, for up to 16 channels with SIMATIC-specific® marking (1 - 20), knife-interruptible terminal block and test socket, module width: 113 mm

VARIOFACE module for Siemens SIMATIC® S7-300, for max. 16 channels with SIMATIC® specific marking (1 - 20), disconnecter terminal and test socket, module width: 113 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2295062

Packing unit 1 pc

Catalog page Page 534 (C-5-2017)

GTIN 4017918339982

Weight per Piece (excluding packing) 251.800 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 113 mm

Height 77 mm

Depth 61 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 60 V DC

Max. perm. current (per branch) 1 A

Max. permissible current (separate power supply) 3 A (per byte)

Number of positions 14

Status display No

Mounting position any

Degree of protection IP00

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection with disconnect knife

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method IDC/FLK pin strip

Number of connections 2

Number of positions 14

Pitch 2.54 mm

Supported controller

Controller GE-FANUC 90-30

- suitable I/O card IC693 MDL732

IC693 MDL733

IC693 MDL740

IC693 MDL741

IC693 MDL742

IC693 ALG220

IC693 ALG221

IC693 ALG222

IC693 ALG223

IC693 ALG390

IC693 ALG391

IC693 ALG392

IC693 ALG442

Controller SIEMENS S7-300 / ET 200 M

- suitable I/O card CPU 312C

CPU 313C-2DP

CPU 314C-2PtP

6ES7 321-1BH50-0AA0

6ES7 321-7BH01-0AB0

6ES7 32...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLKM-2FLK14/KDS3-MT/PPA/S7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.