

**INDUSTRIAL COMPONENT DATA**

# ME 45 UTM GN 2853404 PHOENIX CONTACT Mounting base housing

Brand: PHOENIX CONTACT | Manufacturer Part Number: ME 45 UTM GN



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | ME 45 UTM GN                     |
| Catalog number  | 2853404                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-9AB8096FD8                    |
| Generated       | 2026-07-27                       |

## Product Overview

Mounting base housing

Rail box, Intermediate element, for modular expansion of the housing volume, high design, with ventilation slits, width: 22.6 mm, height: 99 mm, depth: 74 mm, colour: green (6021), cross bridge: without bus connector, number of poles cross connector: not relevant

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 2853404

Packing unit 10 pc

Minimum order quantity 10 pc

Catalog page Page 675 (C-1-2013)

GTIN 4017918173074

Weight per Piece (excluding packing) 14.160 g

Custom tariff number 85389099

Country of origin DE (Germany)

General

Housing type Intermediate element

Housing material Polyamide

Color (RAL) green (6021)

Ambient conditions

Ambient temperature (operation) -40 °C ... 105 °C (depending on power dissipation)

Dimensions

Width 22.5 mm

Depth 99 mm

Technical data

Number of positions 999

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.027180401eCl@ss 4.127180401eCl@ss 5.027180506eCl@ss 5.127180500eCl@ss 6.027180800eCl@ss  
7.027182702eCl@ss 8.027182702eCl@ss 9.027182702

ETIM 2.0EC001031ETIM 3.0EC001031ETIM 4.0EC001031ETIM 5.0EC001031ETIM 6.0EC001031

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.0131261501UNSPSC  
13.231261501

ETIM for 2853404 Low-voltage industrial controls and switchgear (EC002779)

Feature Name

Feature Value

Type of enclosure (EF003086)

Open

Housing connectable (EF003088)

No

Suitable for rail mounting (EF003972)

No

Wall mounting possible (EF003973)

No

With integrated PCB-mounting connection system (EF003087)

No

Material (EF002169)

Other

Surface finishing (EF006569)

Other

RAL-number (EF000116)

6021

Width (EF000008)

22.6 mm

Height (EF000040)

99 mm

Depth (EF000049)

74 mm

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ME 45 UTM GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.