

INDUSTRIAL COMPONENT DATA

IOA REL 230V DI/1.0A/EX 2910423 PHOENIX CONTACT

Input/output module

Brand: PHOENIX CONTACT | Manufacturer Part Number: IOA REL 230V DI/1.0A/EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	IOA REL 230V DI/1.0A/EX
Catalog number	2910423
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-55A11E242E
Generated	2026-08-04

Product Overview

Input/output module

Relay module for Marshalling VIP I/O base elements. For galvanically separating 230 V AC field equipment to digital inputs. Includes fuse and fuse failure indication.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > INTERFACE Components (IF)**

Additional Product Information

Key Commercial Data

Orderkey 2910423

Packing unit 1 pc

Note Made to Order (non-returnable)

GTIN 4055626497303

Weight per Piece (excluding packing) 31.000 g

Custom tariff number 85364900

Country of origin US (United States)

Dimensions

Width 10.3 mm

Height 64.2 mm

Depth 72.9 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
Coil side
Nominal input voltage UN 230 V AC
Input voltage range in reference to UN 0.9 ... 1.1
Typical input current at UN 3 mA
Typical response time 7 ms
Typical release time 15 ms
Protective circuit Bridge rectifier
Operating voltage display Yellow LED
Contact side
Contact type 1 N/O contact
Type of switch contact Single contact
Contact material AgSnO, hard gold-plated
Maximum switching voltage 24 V DC
Min. switching current 1 mA (at 24 V)
Maximum inrush current 50 mA
Limiting continuous current 50 mA
Interrupting rating (ohmic load) max. 1.2 W (at 24 V DC)
General
Operating mode 100% operating factor
Degree of protection IP20
Mechanical service life 2x 10⁷ cycles
Mounting position any
Assembly instructions Plugs into VIP/...BASE...
Net weight (SAP) 31 g
Standards and Regulations
Standards/regulations IEC 60664
DIN EN 50178
Flammability rating according to UL 94 V0
Conformance ANSI/ISA 60079-0; 60079-15
ANSI/IEC 60529
FM 3600; 3611; 3810
ATEX Sira 17ATEX4293X; II 3G Ex nA nC IIC T4 Gc
IECEX IECEX SIR 17.0078X; Ex nA nC IIC T4 Gc
UL, USA/Canada Class I, Div. 2, Groups A, B, C, D T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IOA REL 230V DI/1.0A/EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.