

INDUSTRIAL COMPONENT DATA

IOA REL 24V DI/BFI/1.0A/EX 2910155 PHOENIX CONTACT

Input/output module

Brand: PHOENIX CONTACT | Manufacturer Part Number: IOA REL 24V DI/BFI/1.0A/EX



Manufacturer	PHOENIX CONTACT
MPN / Reference	IOA REL 24V DI/BFI/1.0A/EX
Catalog number	2910155
Category	Switching relay
Minimum order	1 Pcs
Document ID	EO-64AB4F8BCC
Generated	2026-08-03

Product Overview

Input/output module

Relay module for Marshalling VIP I/O base elements. For galvanic separation coupling of 24 V DC field equipment with galvanic separation. Includes fuse and fuse failure indication.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data

Orderkey 2910155

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 556 (C-5-2017)

GTIN 4055626447292

Weight per Piece (excluding packing) 29.700 g

Custom tariff number 85364190

Country of origin US (United States)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 10.3 mm

Height 64.2 mm
Depth 72.9 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 70 °C
Coil side
Nominal input voltage UN 24 V DC
Input voltage range in reference to UN 0.9 ... 1.1
Typical input current at UN 7 mA
Typical response time 5 ms
Typical release time 8 ms
Protective circuit Reverse polarity protection Polarity protection diode
Free-wheeling diode Damping diode
Operating voltage display Yellow LED
Contact side
Contact type 1 N/O contact
Type of switch contact Single contact
Contact material AgSnO, hard gold-plated
Maximum switching voltage 24 V DC
Minimum switching voltage 100 mV (at 10 mA)
Min. switching current 1 mA (at 24 V)
Maximum inrush current 50 mA
Limiting continuous current 50 mA
Interrupting rating (ohmic load) max. 1.2 W (at 24 V DC)
General
Operating mode 100% operating factor
Degree of protection IP20
Mechanical service life 2x 10⁷ cycles
Assembly instructions Plugs into VIP/...BASE...
Net weight (SAP) 29.7 g
Standards and Regulations
Standards/regulations IEC 60664
DIN EN 50178
Flammability rating according t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IOA REL 24V DI/BFI/1.0A/EX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.