

INDUSTRIAL COMPONENT DATA

IPC 16/ 4-ST-10,16 CP1,4 BDNZ 1711022 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: IPC 16/ 4-ST-10,16 CP1,4 BDNZ



Manufacturer	PHOENIX CONTACT
MPN / Reference	IPC 16/ 4-ST-10,16 CP1,4 BDNZ
Catalog number	1711022
Category	Cable connector
Minimum order	25 Pcs
Document ID	EO-CAA25F1BFA
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 16 mm², color: green, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: IPC 16/.. -ST, pitch: 10.16 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - without clamping hook, plug-in system: COMBICON PC 16, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 1711022

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356079389

Weight per Piece (excluding packing) 35.710 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Length [l] 44.1 mm

Width [w] 43.68 mm

Height [h] 27.8 mm

Pitch 10.16 mm

Dimension a 30.48 mm

General

Range of articles IPC 16/..-ST

Number of positions 4

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 1000 V

Connection in acc. with standard EN-VDE

Nominal current IN 76 A

Nominal cross section 16 mm²

Connection data

Conductor cross section solid min. 0.75 mm²

Conductor cross section solid max. 16 mm²

Conductor cross section flexible min. 0.75 mm²

Conductor cross section flexible max. 16 mm²

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 16 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm²

Conductor cross section AWG min. 18

Conductor cross section AWG max. 6

2 conductors with same cross section, solid min. 0.75 mm²

2 conductors with same cross section, solid max. 6 mm²

2 conductors with same cross section, stranded min. 0.75 mm²

2 conductors with same cross section, stranded max. 6 mm²

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IPC 16/ 4-ST-10,16 CP1,4 BDNZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.