

INDUSTRIAL COMPONENT DATA

IPCV 16/ 4-G-10,16 PA1,2,4 1749120 PHOENIX CONTACT

Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: IPCV 16/ 4-G-10,16 PA1,2,4



Manufacturer	PHOENIX CONTACT
MPN / Reference	IPCV 16/ 4-G-10,16 PA1,2,4
Catalog number	1749120
Category	Printed circuit board connector
Minimum order	50 Pcs
Document ID	EO-7A277D3E3E
Generated	2026-08-05

Product Overview

Printed-circuit board connector

Printed circuit board base housing, nominal section: 16 mm², color: green, nominal current: 76 A, nominal voltage (III/2): 1000 V, contact surface: silver, contact type: Female, number of potentials: 3, number of rows: 1, number of poles: 4, number of connections: 3, family of articles: IPCV 16/.. -G, pitch: 10.16 mm, mounting: Wave soldering, pin arrangement: Linear pin arrangement, pin length [P]: 4 mm, number of solder pins per potential: 3, plug-in system: COMBICON PC 16, Plug-in face orientation: Standard, locking: without, fixing type: without, packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1749120

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356311687

Weight per Piece (excluding packing) 12.280 g

Custom tariff number 85366930

Country of origin PL (Poland)

Dimensions

Length [l] 13.6 mm

Width 41.44 mm

Pitch 10.16 mm

Dimension a 30.48 mm

Width [w] 41.44 mm

Height [h] 36.1 mm

Height 32.1 mm

Length of the solder pin 4 mm

Pin dimensions 0.8 x 1.2 mm

Length 13.6 mm

General

Range of articles IPCV 16/..-G

Rated voltage (III/3) 1000 V

Nominal current I_N 76 A

Color green

Number of positions 4

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 4.0272607xxeCl@ss 4.127260701eCl@ss 5.027260701eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss

7.027440402eCl@ss 8.027440402eCl@ss 9.027440402

ETIM 3.0EC001121ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637

UNSPSC 6.0130211810UNSPSC 7.090139121409UNSPSC 1139121409UNSPSC 12.0139121409UNSPSC

13.239121409

ETIM for 1749120 Connectors (EC002637)

Feature Name

Feature Value

Connector model (EF007495)

Fixed connector

Contact type (EF001587)

Bus

Number of poles (EF001391)

3

Number of plug-in contact rows (EF006935)

1

Modular spacing contacts (EF007326)

10.16 mm

Modular spacing connections (EF006827)

10.16 mm

Rated current I_n (EF008250)

76 A

Rated voltage (EF000228)

1000 V

Rated surge voltage (EF002993)

8 kV

Over voltage category (EF006785)

III

Pol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / IPCV 16/ 4-G-10,16 PA1,2,4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.