

INDUSTRIAL COMPONENT DATA

ISPC 5/ 4-STGCL-7,62BKBD2PEQSO 1715192 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: ISPC 5/ 4-STGCL-7,62BKBD2PEQSO



Manufacturer	PHOENIX CONTACT
MPN / Reference	ISPC 5/ 4-STGCL-7,62BKBD2PEQSO
Catalog number	1715192
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-6971000802
Generated	2026-08-02

Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 6 mm², color: black, nominal current: 41 A, nominal voltage (III/2): 1000 V, contact surface: Tin, contact type: Male, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: ISPC 5/.. -STGCL, pitch: 7.62 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, clamping hook: - without clamping hook, plug-in system: COMBICON PC 5, locking: Clip lock, fixing type: Click & Lock locking window, packaging type: boxed

PCB connector, nominal cross section: 6 mm², color: black, nominal current: 41 A, rated voltage (III/2): 1000 V, contact surface: Sn, contact connection type: Pin, number of potentials: 4, number of rows: 1, number of positions: 4, number of connections: 4, product range: ISPC 5/..-STGCL, pitch: 7.62 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON PC 5, locking: Clip locking, mounting: Click & Lock latching window, type of packaging: packed in cardboard

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Technical dataProduct propertiesProduct type PCB connector

Product family ISPC 5/..-STGCL

Product line COMBICON Connectors L

Number of positions 4

Pitch 7.62 mm

Number of connections 4
Number of rows 1
Number of potentials 4
Data management status
Article revision 00
Electrical propertiesNominal current IN 41 A
Nominal voltage UN 1000 V
Contact resistance 0.55 mΩ
Rated voltage (III/3) 1000 V
Rated surge voltage (III/3) 8 kV
Rated voltage (III/2) 1000 V
Rated surge voltage (III/2) 8 kV
Rated voltage (II/2) 1000 V
Rated surge voltage (II/2) 6 kV
Connection dataConnection technology
Type Inverted
Connector system COMBICON PC 5
Nominal cross section 6 mm²
Contact connection type Pin
Interlock
Locking type Clip locking
Mounting flange Click & Lock latching window
Conductor connection
Connection method Push-in spring connection
Conductor/PCB connection direction 0 °
Conductor cross section rigid 0.2 mm² ... 10 mm²
Conductor cross section flexible 0.2 mm² ... 6 mm²
Conductor cross section AWG 24 ... 8
Conductor cross section flexible, with ferrule without plastic sleeve 0.25 mm² ... 6 mm²
Conductor cross section, flexible, with ferrule, with plastic sleeve 0.25 mm² ... 4 mm²
2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 0.25 mm² ... 1.5 mm²
Cylindrical gauge a x b / diameter 4.3 mm x 4.0 mm / 4.0 mm
Stripping length 15 mm
Specifications for ferrules without insulating collar
recommended crimping tool 1212034 CRIMPFOX 6
1213144 CRIMPFOX CE...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ISPC 5/ 4-STGCL-7,62BKBD2PEQSO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.