

INDUSTRIAL COMPONENT DATA**FBS 4-3,5 GY 3213180 PHOENIX CONTACT Plug-in bridge**

Brand: PHOENIX CONTACT | Manufacturer Part Number: FBS 4-3,5 GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	FBS 4-3,5 GY
Catalog number	3213180
Category	Cross-connector for terminal block
Minimum order	50 Pcs
Document ID	EO-63C28786CC
Generated	2026-08-05

Product Overview

Plug-in bridge

Plug-in bridge, pitch: 3.5 mm, colour: grey

Plug-in bridge, pitch: 3.5 mm, number of positions: 4, color: gray

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **PHOENIX CONTACT > Modular TBs****Additional Product Information**

Technical dataProduct propertiesProduct type Jumper

Number of positions 4

Pitch 3.5 mm

Data management status

Article revision 03

Electrical propertiesMaximum load current 17.5 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

Connection dataMaximum load current 17.5 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

DimensionsPitch 3.5 mm

Material specificationsColor gray (RAL 7042)

Material Copper

Flammability rating according to UL 94 V0

Insulating material PA

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (operation) 20 % ... 90 %

Permissible humidity (storage/transport) 30 % ... 70 %

Mounting Mounting type Plug-in mounting

ETIM for 3213180 Terminal blocks (EC000489)

Feature Name

Feature Value

Explosion-tested version 'Ex e' (EF008498)

No

Mounting method (EF000003)

Pluggable

Modular spacing (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FBS 4-3,5 GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.