

## INDUSTRIAL COMPONENT DATA

# K-7E-M17 M9/5,0-D01/M17 F8 1619324 PHOENIX CONTACT

## Connector in molded plastic on both sides

Brand: PHOENIX CONTACT | Manufacturer Part Number: K-7E-M17 M9/5,0-D01/M17 F8



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                               |
| MPN / Reference | K-7E-M17 M9/5,0-D01/M17 F8                    |
| Catalog number  | 1619324                                       |
| Category        | Power cable less 1 kV, for moving application |
| Minimum order   | 2 Pcs                                         |
| Document ID     | EO-7BCD813FA9                                 |
| Generated       | 2026-08-04                                    |

### Product Overview

Connector in molded plastic on both sides

Plug-in connector coated with plastic on both sides, series: KST, M17-Female, straight coated by plastic extrusion, number of poles: 7+PE, Lock type: Screw lock, to M17-Male, straight coated by plastic extrusion, number of poles: 7+PE, cable length: 5 m, shielded: yes, outer wrap color: orange RAL 2003

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

### Additional Product Information

Key Commercial Data

Orderkey 1619324

Packing unit 1 pc

Minimum order quantity 2 pc

Note Made to Order (non-returnable)

Catalog page Page 225 (C-2-2017)

GTIN 4046356830652

Weight per Piece (excluding packing) 1,113.000 g

Custom tariff number 85444290

Country of origin DE (Germany)

Conductor length 5 m

Nominal current 15 A

**Connector specifications**

Type straight plastic-sheathed

Housing material Zinc die-cast

Thread type M17

Locking type Screw locking

Degree of protection IP67, when in locked state

Number of positions 7+PE

Direction of rotation Standard

Type of contact Socket

Insertion/withdrawal cycles 50

Contact resistance &lt; 0.3 mΩ

Max. current 14 A

Voltage 630 V

Overvoltage category III

Degree of pollution 3

Rated surge voltage 6 kV

Ambient temperature (operation) -40 °C ... 105 °C

**Cable specifications**

Type of cable PSLC11Y-J

Shielded yes

Cable structure 4 x 1 mm<sup>2</sup> + 2 x 2 x 0.75 mm<sup>2</sup> StC

Cable structure (AWG) 18 AWG/4c + 19 AWG/2pr

External cable diameter 11 mm

Outer sheath, material PUR

Material wire insulation TPM

External sheath, color orange RAL 2003

Nominal voltage, cable 1000 V

Test voltage 4 kV (2 kV signal)

Rated current 15 A

Smallest bending radius, movable installation 110 mm

Ambient temperature for fixed installation -40 °C ... 80 °C

Ambient temperature for flexible installation -20 °C ... 60 °C

**Connector specifications (second page)**

Type straight plastic-sheathed

Housing material Zinc die-cast

Thread type M17

Degree of protection IP67, when in locked state

Number....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-7E-M17 M9/5,0-D01/M17 F8 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.