

INDUSTRIAL COMPONENT DATA

K-8E-M23F8/2,0-H00/M23F8-C5-S 1508135 PHOENIX CONTACT

Plug-in connector coated with plastic on both sides, s..

Brand: PHOENIX CONTACT | Manufacturer Part Number: K-8E-M23F8/2,0-H00/M23F8-C5-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	K-8E-M23F8/2,0-H00/M23F8-C5-S
Catalog number	1508135
Category	Power cable less 1 kV, for moving application
Minimum order	50 Pcs
Document ID	EO-2682630B3E
Generated	2026-08-04

Product Overview

Plug-in connector coated with plastic on both sides, series: KSH, M23-Female, straight coated by plastic extrusion, number of poles: 4+4+4+PE, lock type: SPEEDCON, cable length: 2 m, shielded: yes, outer wrap color: orange RAL 2003

Plastic coated cable plug

Cable plug in molded plastic

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataProduct propertiesProduct type Signal and power cable

ETIM for 1508135 Cable (EC003250)

Feature Name

Feature Value

AWG size (EF011789)

Other

Screen over stranding element (EF001623)

None

With protective conductor (EF007468)

No

Suspension element (EF001794)

Other

Torsion resistant (EF001687)

No

Low smoke according to EN IEC 61034-2 (EF003799)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-8E-M23F8/2,0-H00/M23F8-C5-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.