

INDUSTRIAL COMPONENT DATA

KC-88014311/20,00 1622080 PHOENIX CONTACT Hybrid cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: KC-88014311/20,00



Manufacturer	PHOENIX CONTACT
MPN / Reference	KC-88014311/20,00
Catalog number	1622080
Category	Power cable less 1 kV, for moving application
Minimum order	1 Pcs
Document ID	EO-BA544E6E2C
Generated	2026-08-06

Product Overview

Hybrid cable

Hybrid cable, series: KSH, M23-Female, straight coated by plastic extrusion, number of poles: 4+4+4+PE, Lock type: SPEEDCON, cable length: 20 m, shielded: yes, outer sheath color: orange RAL 2003

Hybrid cable, cable length: 20 m, shielded: yes, color of outer sheath: orange RAL 2003

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Technical dataNotesNotes on operation Observe derating curve.

Product propertiesProduct type Cable by the meter

ConnectorCable specifications

Cable type HDSL11Y-J

Transmission speed CAT5

Transmission speed 100 Mbps (Data interface)

Shielded yes

Cable structure (5x 2.5 + 2x (2x 0.5) + (4x 0.34)C) C

External cable diameter 15.50 mm ±0.5 mm

Outer sheath, material PUR

Material wire insulation TPE

External sheath, color orange RAL 2003

Single wire, color black 1, black 2, black 3, black 4, green/yellow Power wires + PE

brown, violet, black 5, green Signal wires

blue, yellow, white, orange Data wires

Nominal voltage, cable 1000 V (300 V signal)

Test voltage 4 kV (1.5 kV signal)

Rated current 26 A (Power, in accordance with DIN VDE 0298-4 Tab. 11/5, at 15°C)

8 A (Signal, according to DIN VDE 0298-4 tab. 11/5)

3.6 A (Data, according to DIN VDE 0298-4 tab. 11/5)

Smallest bending radius, fixed installation 73 mm

Smallest bending radius, movable installation 148 mm

Max. bending cycles 1000000

Traversing path 6 m

Acceleration 30 m/s²

Ambient temperature (operation) for fixed installation -40 °C ... 80 °C (fixed installation)

Ambient temperature (operation) for flexible installation -20 °C ... 80 °C (flexible installation)

UL AWM style 20234 / 10492 (80°C/1000 V)

Special properties Flexible cable conduit capable

Flame resistance IEC 60332-1-2

Halogen-free in accordance with EN 50267-2-1

Resistance to oil EN 60811-2-1

Cable/line Cable length 20 m

ETIM for 1622080 Cable (EC003250)

Feature....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / KC-88014311/20,00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.