


INDUSTRIAL COMPONENT DATA

PT 1,5/S-QUATTRO-MT 3210321 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 1,5/S-QUATTRO-MT



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 1,5/S-QUATTRO-MT
Catalog number	3210321
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-4EF79C7677
Generated	2026-08-03

Product Overview

Knife disconnect terminal block

Blade interruptible terminal block, nominal voltage: 400 V, nominal current: 10 A, 1st floor, connection type: Push-in connection, Dimensioning cross-section: 1.5 mm², cross-section: 0.14 mm² - 1.5 mm², mounting: NS 35/7.5, NS 35/15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 3210321

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 40 (C-1-2017)

GTIN 4046356905664

Weight per Piece (excluding packing) 6.240 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 1

Number of connections 4

Potentials 1Nominal cross section 1.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.56 W

Maximum load current 10 A

Nominal current I_N 10 ANominal voltage U_N 400 V

Open side panel Yes

Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 7.3 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.89 kV

Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending test conductor cross section/weight 0.14 mm² / 0.2 kg1.5 mm² / 0.4 kg

Tensile test result Test passed

Conductor cross section tensile test 0.14 mm²

Tractive force setpoint 10 N

Conductor cross section tensile test 1.5 mm²

Tractive force setpoint 40 N

Result of tight fit on support Test passed

Tight fit on carrier NS 35

Setpoint 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 1,5/S-QUATTRO-MT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.