


INDUSTRIAL COMPONENT DATA

UTT 2,5-2MT-P/P 3044670 PHOENIX CONTACT Knife disconnect terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UTT 2,5-2MT-P/P



Manufacturer	PHOENIX CONTACT
MPN / Reference	UTT 2,5-2MT-P/P
Catalog number	3044670
Category	(Knife) disconnect terminal block
Minimum order	50 Pcs
Document ID	EO-AFB8D2E4A1
Generated	2026-08-02

Product Overview

Knife disconnect terminal block

Blade interruptible terminal block, with threaded sockets for test sockets to accommodate test pins, nominal voltage: 400 V, nominal current: 16 A, connection type: Screw connection, Sizing section: 2.5 mm², section: 0.14 mm² - 4 mm², connection type: Screw connection, Sizing section: 2.5 mm², section: 0.14 mm² - 4 mm², Mounting: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3044670

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 222 (C-1-2017)

GTIN 4046356894081

Weight per Piece (excluding packing) 22.730 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Number of levels 2

Number of connections 4

Nominal cross section 2.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 16 A
Maximum load current 16 A (in case of a 4 mm² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)
Nominal voltage U_N 400 V
Open side panel Yes
Shock protection test specification DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 7.3 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.14 mm² / 0.2 kg
2.5 mm² / 0.7 kg
4 mm² / 0.9 kg
Tensile test result Test passed
Conductor cross section tensile test 0.14 mm²
Tractive force setpo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UTT 2,5-2MT-P/P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.